# Parallel Guide KIT

Osstem Surgical Guide



Prime KIT: OPGPK (options excluded)

Advanced KIT: OPGAK (including all options)



## Composition of Lower Valve



## **Guide Drill**

- · Initial drill: fastened to the single guide for initial drilling, and enables drilling to be stoppedat a depth of 7 mm
- · Twist drill: used with bridge guide for initial drilling, and enables to the depth to be adjusted by referencing marking

D	Ø2.2				
Initial drill	GD2208NC				
Twist drill	GS2213FNC				
	Initial drill				
	Twist drill				

# **Single Guide**

- · Transparent material used to recognize location and direction of drilling
- · Function of initial drill stops at 7 mm depth
- · 6-type composition from Ø 5.0 to 10.0 based on mesio-distal crown diameter

Guide Pin

\	D	Ø5.0	Ø6.0	Ø7.0	Ø8.0	Ø9.0	Ø10.0
		SGB050	SGB060	SGB070	SGB080	SGB090	SGB100
	Ø5.	0 9	Ø6.0	Ø7.0	Ø8.0	Ø9.0	Ø10.0

#### **Guide Pin**

· Checking the path on the drilling site and fixing the single guide

PGSP22



# **Bridge Guide**


- · Adjusting distance and direction of drilling
- · Fan type: selecting from 7.0 12.5 mm interval, in increments of 0.5 mm
- · Compass type: adjustable from5 24 mm interval, in increments of1 mm
- · Use after controlling distance in the distance setup at the middle plate of KIT

Type \ Distance	7~8.5	9~10.5	11~12.5	5~24
Fan	PGBRA070	PGBRA090	PGBRA110	=
Compass	-	-	-	PGBPA





Compass type Option



Bridge guideisfan-shaped, enabling easy adjustment of distance

Single Guide

#### **Multi Joint Handle Option**

• Equipment to hold the location of guide from out of mouth by being connected to the ball head of the Bridge guide

MJH



## **Denture Guide Option**

- $\cdot$  Angle of guide is adjustable for each individual patient in cases of edentulous jaw
- Oral drilling while fixing the angle with the L-wrench on the plaster cast according to the dental arch shape of patient

PGODA







## L-wrench Option

· Equipment to firmly fix the Denture guide after adjusting the size

LWC20H



## **DEUTSCHE OSSTEM GmbH**

Mergenthalerallee 25, 65760 Eschborn, Germany Tel: +49(0)6196 777 550 Fax: +49(0)6196 777 5529

E-mail: info@osstem.de www.osstem.de